



## SL-1LED SPECIFICATIONS FAA-810 LED SIDELIGHT

Intensity	Low
Horizontal Coverage	360°
Vertical Beam	10° Minimum
Lamp Description	(1) 2 Luxeon Star Led
Effective Candelas	32.5 Minimum
Height	7.5"
Diameter	4.875"
Fixture Base Material	Aluminum A-356
Led Housing Material	Powder Coated Aluminum (red) and Glass
Voltage	120VAC 60 HZ (Available in other voltages)
Wattage	8 Watts
Weight	3 lbs.
Operating Temperature	-55 C° to +55 C°
Wind Load	CAAA= 0.2 FT2
Mounting Holes	0.75", 1", Or 1.25" NPT (Both side and bottom hub)
Hardware Material	Stainless Steel

### QUALITY:

- No preventive maintenance required after proper installation.
- Resistant to heavy rain or storms and corrosion.
- Resistant to shock and vibration.

### ADVANTAGES:

- 95% less power consumption than incandescent light.
- 50 times more life compared to incandescent light.
- ETL certified to FAA (AC-150/5345-43F)
- 5 year warranty.
- Direct replacement for existing incandescent sidelights.
- Aluminum base (no plastic).

### IMPORTANT:

- This fixture has (2) options of mounting (side and bottom hub) allowing the customer to choose a mounting preference without alerting the fixture.
- Technical service available 24/365.
- The use of non-OEM parts will void warranty.