

## GROUNDING PRODUCTS

# GROUND ACCESS WELLS

**Light Duty Ground Access Well**

| Catalog Number | Diameter (in) | Length (in) | Cover Type               |
|----------------|---------------|-------------|--------------------------|
| PE6AHDH00L74   | 6             | 9           | HDPE                     |
| PE9AHDH00L74   | 9             | 10          | HDPE                     |
| PE10HDH00L74   | 10            | 18.875      | HDPE                     |
| PE10UPH00009   | 10            | 18.25       | Steel                    |
| 38-8130-02     | 10            | 19          | Steel with Steel/PC Ring |

\*\*



\*\*SE OFERTA EL MODELO PE9AHD00L74 DE 9X10PULGADAS

### MATERIAL SPECIFIC INFORMATION:

- Widely used in Electric, CATV, Telephone, and Water Industries
- Base made of high density polyethylene structural foam
- All stainless steel hardware, including captive bolts
- Rigid enclosure and cover are lightweight and easy to handle

### HDDE ( High Density Polyethylene)

- Thermal Shock ASTM D-756
- Water Absortion ASTM D-570 Section 6.1
- Weathering ASTM D-822 Sec 6.2 Proc A
- Chemical Resistance ASTM D-543
- Flammability-Union Carbide Method WC-73-D-1

Contact thermOweld for other options

### APPLICATION NOTES:

- Provides ready access to ground electrode for testing and inspection purposes.
- To prevent displacement by frost, the access well must be longer than the frost line is deep.

+1 (918) 627-5210 • 1-800-558-1373 • WWW.THERMOWELD.COM