



- 工作温度: -40 ~ +140
Operating Temperature: -40 ~ +140
- 嵌件: 黄铜.铁
Insert: Brass. Steel with Zn coating
- 材料: 不饱和聚酯树脂玻璃纤维增强模压塑料(BMC)(SMC)
Material: BMC (Bough Moulding Compound)
SMC(Sheet Moulding Compound)
- 颜色、嵌件、材料性能可依客户需求定制
Colour, Insert, material In capability accordance with customer needs

■ U4535S 外观及尺寸(mm)

伸缩强度(LBS) Tensile strength(LBS)	650
耐压(KV) Voltage withstand(KV)	6
扭矩(FT LBS) Torgue strength(FT LBS)	12
螺纹(mm) screw(mm)	10 UNC3/8-16
螺纹深度(mm) screw depth(mm)	12

■ U4535 外观及尺寸(mm)

伸缩强度(LBS) Tensile strength(LBS)	700
耐压(KV) Voltage withstand(KV)	6
扭矩(FT LBS) Torgue strength(FT LBS)	12
螺纹(mm) screw(mm)	10 UNC3/8-16
螺纹深度(mm) screw depth(mm)	12

■ U4538 外观及尺寸(mm)

伸缩强度(LBS) Tensile strength(LBS)	800
耐压(KV) Voltage withstand(KV)	8
扭矩(FT LBS) Torgue strength(FT LBS)	12
螺纹(mm) screw(mm)	10 UNC3/8-16
螺纹深度(mm) screw depth(mm)	12

■ U5258 外观及尺寸(mm)

伸缩强度(LBS) Tensile strength(LBS)	1000
耐压(KV) Voltage withstand(KV)	10
扭矩(FT LBS) Torgue strength(FT LBS)	30
螺纹(mm) screw(mm)	10 UNC3/8-16
螺纹深度(mm) screw depth(mm)	15

■ U6367 外观及尺寸(mm)

伸缩强度(LBS) Tensile strength(LBS)	1000
耐压(KV) Voltage withstand(KV)	12
扭矩(FT LBS) Torgue strength(FT LBS)	40
螺纹(mm) screw(mm)	10 UNC5/8-16
螺纹深度(mm) screw depth(mm)	15