



# Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 75kVA

By Acme Electric  
Catalog # [T3075K0013B](#)

Low Voltage Distribution Transformer - Three Phase, 480Δ - 208Y/120V, 75kVA



### Features

- Quiet operation with sound levels below NEMA standards

### Specifications

|                           |                                          |
|---------------------------|------------------------------------------|
| Dept of Energy Regulation | Meets or exceed U.S. DOE 10 CFR Part 431 |
| CSA Standard              | C22.2 No. 47                             |
| Nema Rating               | NEMA 3R                                  |
| UL Standard               | UL 1561                                  |
| Buy America(n) Qualified  | Contact Manufacturer                     |
| UL Insulation Class       | 220°C                                    |

### Configuration

|           |   |
|-----------|---|
| ANFC Taps | 2 |
|-----------|---|

### Current

|                   |            |
|-------------------|------------|
| Frequency Rating  | 60 Hz      |
| Efficiency        | 98.60%     |
| Primary Voltage   | 480D V     |
| kVA               | 75.0       |
| Primary Voltage   | 480Δ       |
| Secondary Voltage | 208Y/120 V |

### Dimensions

|        |          |
|--------|----------|
| Length | 22.37 in |
|--------|----------|

|            |                                |
|------------|--------------------------------|
| Weight     | 500 lb.                        |
| Height     | 29.41 in                       |
| Width      | 28.15 in                       |
| Dimensions | 22.37 in x 28.15 in x 29.41 in |

### General

|                  |                                   |
|------------------|-----------------------------------|
| Product Category | Dry Type Distribution Transformer |
| Material type    | ZFIN                              |
| Taps % Steps     | 2.5%                              |
| Winding Material | AL                                |
| BNFC Taps        | 4                                 |
| Mounting Type    | Floor                             |
| UPC              | 047503091142                      |
| Construction     | Ventilated                        |

### Logistics

|                 |   |
|-----------------|---|
| Pallet Quantity | 1 |
| Carton Quantity | 1 |

### Operational

|                      |                     |
|----------------------|---------------------|
| Max Temperature Rise | 150 Degrees Celsius |
|----------------------|---------------------|

### Product Assets

[Catalog \[English\]](#)